

'2 3 / \$ 6 6 , & , & 2 5 ( & 7 , ) , ( 5 6

<p>) HDWXUHV                  "Plastic package has Underwrites Laboratory                  ) ODPPELOLW\ &amp; ODVVLILFDWLRQ 9                  "Fast switching speed                  "Diffused junction                  "High current capability                  "High temperature soldering guaranteed: 250¥ /10 seconds,                  0.375"(9.5mm)lead length,5lbs.(2.3kg)tension                    " &amp; DVH - ("2&amp; PRO SHOD E WGF                  " 3 RODUL W D &amp; SHOD E WGF                  " ORXQ W R Q U W L R Q \$ Q \</p>	
---	--

0 \$ ; , 0 8 0 5 \$ 7 , 1 \* 6 \$ 1 ' & + \$ 5 \$ & 7 ( 5 , 6 7 , & 6

# f & \$ P E L H E W S H U D X Q Q R H W K H U Z R L W H G

			¥\$	¥\$	¥\$
7<3( 180%(5					
0D[LPXP UHSHWLWLYH SHDN UHYH 95/50 YROWDJH	9506	9			
0D[LPXP 506 YROWDJH	9506	9			
0D[LPXP ' & EORFNLQJ YROWDJH	9' &	9			
	,) \$9	\$			
	)60	\$			
2SHUDWLQJ MXQFWLRQ WHPSHUDWXUH UDQJH	7VWJ			WR	
6WRUDJH WHPSHUDWXUH UDQJH	7VWJ			WR	
0D[LPXP LQVWDQWDQHRXV IRUZDUG YROWDJH DW \$				0D[	
			\$	0D[	0D[LPXP B